

Softlite 440 & 640 Portable Lighting Solutions



The **Softlite 440** is ideal for use on any project where space is at a minimum. Its lightweight and compact design allows light to be moved quickly and safely to required areas and it is one of the quietest lighting solutions on the market.

Available from 110 – 230V the system is lightweight and robust, weighing just 8kg and measuring just 910mm in length. With an illumination area of 1500m², Softlite is the optimal temporary lighting solution for onsite projects where wide reaching light is required, yet space is at a premium.

MODEL	440
ENERGY EFFICIENT INDUCTION LAMPS	55W
NO. OF LAMPS	8
TOTAL LIGHTING OUTPUT	440W
POWER OF ELECTRICITY SUPPLY	464W
RFI SUPPRESSED ELECTRONIC BALLASTS	Yes
SUPPLY LEAD	10m
IMMEDIATE ILLUMINATION	Yes
TIME TO REACH TEMPERATURE	2 mins
PROTECTION INDEX	IP 44
WIND RESISTANCE	162 km/h
TEMPERATURE RANGE FOR USE	-15°/+40°
AREA OF ILLUMINATION	1500m ²
COLOUR TEMPERATURE	6500°K
LUMENS	38400
DIAMETER	225mm
LENGTH	910mm
WEIGHT	8kg
OPTIMAL HEIGHT FOR USE	3m
AVERAGE ASSEMBLY TIME	2mins

Features:

- **8 x 55W lamps** - 1,500m² area of lighting with 440W output
- **Lamps installed in pairs** to ensure constant light
- **Anti-shock plexi-glass plastic** is resistant to adverse weather conditions
- **ABS composite plastic base** is light, robust, quick and easy to assemble



Options and accessories:

- Telescopic mast with or without winch
- Carry Bag Switch for 180° illumination
- Hinge +/- 15°
- Suspension cradle
- 700W generator
- Coloured diffuser tubes
- Mast with guy wires

Applications



Specifications are subject to change without prior notice





Retaining all of the lightweight and compact features of the Softlite 440, at 230V the **Softlite 640** is the most powerful model in the range, lighting an area of up to 2,400m² with a powerful output of 640W.

Ideal for any project where space is at a premium, the **Softlite 640** offers powerful light, with no glare or shadows, without compromising on versatility and space. Weighing just 8.5kg and measuring just 910mm in length it is the ultimate versatile lighting solution.

ELECTRICAL SPECIFICATIONS	640
ENERGY EFFICIENT INDUCTION LAMPS	80W
NO. OF LAMPS	8
TOTAL LIGHTING OUTPUT	640W
POWER OF ELECTRICITY SUPPLY	664W
RFI SUPPRESSED ELECTRONIC BALLASTS	Yes
SUPPLY LEAD	10m
IMMEDIATE ILLUMINATION	Yes
TIME TO REACH TEMPERATURE	3 mins
PROTECTION INDEX	IP 44
WIND RESISTANCE	162 km/h
TEMPERATURE RANGE FOR USE	-15°/+40°
AREA OF ILLUMINATION	2400m ²
COLOUR TEMPERATURE	4000°K
LUMENS	52000
DIAMETER	225mm
LENGTH	910mm
WEIGHT	8.5kg
OPTIMAL HEIGHT FOR USE	3m
AVERAGE ASSEMBLY TIME	2mins

- Features:**
- **8 x 80W lamps** - 2,400m² area of lighting with 640W output
 - **Lamps installed in pairs** to ensure constant light
 - **Anti-shock plexi-glass plastic** is resistant to adverse weather conditions
 - **ABS composite plastic base** is light, robust, quick and easy to assemble



Options and accessories:

- Telescopic mast with or without winch
- Carry Bag Switch for 180° illumination
- Hinge +/- 15°
- Suspension cradle
- 1000W generator
- Coloured diffuser tubes
- Mast with guy wires